

## 15.6" Fanless POS terminal Low Consumption



### General:

**It has a different design concept it's 16:9 ratio, it is designed with optimum configuration and the point-of-sale components: Intel new Baytrail motherboard, fanless design, Mitsubishi new LED panels, etc.. It's suitable for all types of enterprise: catering, retail, entertainment, business.**

**Features:**

1. Fanless design, less heat, long-lasting performance, low consumption.
2. Intel Baytrail mainboard
3. Mitsubishi LED new Panel with high brightness.
4. Not easy to get into dust.
5. Good viewing angle.
6. OEM project is welcomed.

## Technical Specifications

|                        |                                                                              |
|------------------------|------------------------------------------------------------------------------|
| DisplayType            | 15.6" Brand new LED touch POS                                                |
| Color                  | Black                                                                        |
| CPU                    | Intel Celeron J-1800, J1900 optional Dual-core, clock speed 1.89G, TDP13W    |
| Main Board             | Intel Baytrail mother board                                                  |
| Memory                 | 2G( 4G optional)                                                             |
| Harddisk               | 32G SSD ( 64G SSD & 500GHDD optional)                                        |
| Interface              | 4 USB, 2 RS232, 1 VGA, 1 LAN, 1 HDMI1 microphone, 1 earphone, 1 power button |
| Resolution             | 1024*768 optional                                                            |
| Brightness             | 250cd/m2                                                                     |
| Touch screen           | 5-wires resistive touch screen                                               |
| View Angle             | monitor Horizon: 160° Vertical:                                              |
| TiltingAngle           |                                                                              |
| Operating Temperature: | 0℃~40℃                                                                       |
| Storage Temperature:   | -20℃~60℃                                                                     |
| Operating System       | Win7, Win8, Windows XP                                                       |
| Driver CD              | 1*CD disk for motherboard and touch function                                 |
| Power adaptor          | 110-240V/50-60HZ AC power input, DC12V/5A output                             |